



PROFESSIONAL

CUTTING DISCS

Applications

- Unalloyed and alloyed construction steel
- High alloy special steel
- Stainless sheet steel
- Non-ferrous metals

Types

- T 41
- T 42

Tool


- Angle Grinder

Advantages

- Durable
- Productive
- Cost efficient
- Reduced heat generation
- Treated against moisture for longer life time

TECHNICAL DATA

		Max R.P.M
APT11151022	22.2 × 1.0 × 115	13300
APT11251022	22.2 × 1.0 × 125	12200
APT112301922	22.2 × 1.9 × 230	6650
APT11801622	22.2 × 1.6 × 180	8500
APT122301922	22.2 × 1.9 × 230	6650



Applications

- Unalloyed and alloyed construction steel
- High alloy special steel
- Angular steel profiles
- Stainless steel

Types

- T 41
- T 42

Tool


- Angle Grinder

Advantages

- Durable
- Productive
- Cost efficient
- Reduced heat generation
- Treated against moisture for longer life time

TECHNICAL DATA

		Max R.P.M
APT21153022	22.2 × 3.0 × 115	13300
APT21253022	22.2 × 3.0 × 125	12200
APT21803022	22.2 × 3.0 × 180	8500
APT22303022	22.2 × 3.0 × 230	6650



Applications

- Unalloyed and alloyed construction steel
- High alloy special steel
- Angular steel profiles
- Stainless steel

Types

- T 27

Tool

- Angle Grinder

Advantages

- Extended life time
- High quality abrasive grain
- Easy working
- Cost efficient
- High stock removal rate

TECHNICAL DATA

		Max R.P.M
APT71256022	22.2 × 6.0 × 125	12200
APT71806022	22.2 × 6.0 × 180	8500
APT72306022	22.2 × 6.0 × 230	6650

INDUSTRIAL

CUTTING DISCS

Applications

- Unalloyed and alloyed construction steel
- High alloy special steel
- Angular steel profiles
- Stainless steel

Types


- T 41
- T 42

Tool

- Angle Grinder


Advantages

- Durable
- Productive
- Cost efficient
- Reduced heat generation
- Treated against moisture for longer life time



TECHNICAL DATA

		Max R.P.M
APT11151022	22.2 × 1.0 × 115	13300
APT11251022	22.2 × 1.0 × 125	12200
APT11251622	22.2 × 1.6 × 125	12200
APT11801622	22.2 × 1.6 × 180	8500
APT112301922	22.2 × 1.9 × 230	6650
APT122301922	22.2 × 1.9 × 230	6650



Applications

- Unalloyed and alloyed construction steel
- High alloy special steel
- Angular steel profiles
- Stainless steel

Types

- T 41
- T 42

Tool

- Angle Grinder

Advantages

- Durable
- Productive
- Cost efficient
- Reduced heat generation
- Treated against moisture for longer life time

TECHNICAL DATA

		Max R.P.M
APT12153022	22.2 × 3.0 × 115	13300
APT121253022	22.2 × 3.0 × 125	12200
APT181803022	22.2 × 3.0 × 180	8500
APT122303022	22.2 × 3.0 × 230	6650



Applications

- Unalloyed and alloyed construction steel
- High alloy special steel
- Stainless sheet steel
- Non-ferrous metals

Types

- T 27

Tool

- Angle Grinder

Advantages

- Extended life time
- High quality abrasive grain
- Easy working
- Cost efficient
- High stock removal rate

TECHNICAL DATA

		Max R.P.M
APT171256022	22.2 × 6.0 × 125	12200
APT171806022	22.2 × 6.0 × 180	8500
APT172306022	22.2 × 6.0 × 230	6650

ABRASIVES BROCHURE

The Name You Can Trust

www.apl-international.com

INDUSTRIAL EXTREME

CUTTING DISCS

Applications

- Unalloyed and alloyed construction steel
- High alloy special steel
- Angular steel profiles
- Stainless steel

Types

- T 41
- T 42

Tool

- Angle Grinder

Advantages

- Durable
- Productive
- Cost efficient
- Reduced heat generation
- Treated against moisture for longer life time



TECHNICAL DATA

Key	Icon	Max R.P.M.
APT11251822	22.2 x 1.6 x 125	12200

CUT-OFF DISCS

PROFESSIONAL

Applications

- 8mm I-steel Rails
- Thin-walled tubes
- Unalloyed and alloyed steel
- High alloy special steel
- Angular steel profiles

Types

- T 41

Tool

- Fixed Cutting Bench

Advantages

- Durable
- Productive
- Cost efficient
- Reduced heat generation
- Less noise



TECHNICAL DATA

Key	Icon	Max R.P.M.
APT13503525	25.4 x 3.5 x 350	4400
APT13504025	25.4 x 4.0 x 350	4400

INDUSTRIAL

Applications

- 8mm I-steel Rails
- Thin-walled tubes
- Unalloyed and alloyed steel
- High alloy special steel
- Angular steel profiles

Types

- T 41

Tool

- Fixed Cutting Bench

Advantages

- Durable
- Productive
- Cost efficient
- Reduced heat generation
- Less noise



TECHNICAL DATA

Key	Icon	Max R.P.M.
APT113003525	25.4 x 3.5 x 300	5100
APT113503525	25.4 x 3.5 x 350	4400
APT113504025	25.4 x 4.0 x 350	4400

PROFESSIONAL

ALUMINIUM OXIDE

Features

Aluminum Oxide/
zirconia grain
Fiberglass backing
Heavy X-weight backing
Available with 11-"8/5 threaded hub



Applications



Conical shaped flaps are angled at 10° which is ideal for contour and edge work. Angled flaps provide greater surface contact for a more aggressive cut. Most efficient when used between 15° to 25° angle.

TECHNICAL DATA Type 29

Key	Icon	Grit
DW427106	115x22.23	60
DW427108	115x22.23	80
DW427304	125x22.23	40
DW427306	125x22.23	60
DW427308	125x22.23	80
DW427310	125x22.23	100
DW427312	125x22.23	120

ALUMINIUM OXIDE

Features

Aluminum Oxide /
Zirconia grain
Fiberglass backing
Heavy X-weight backing
Available with 11-"8/5 threaded hub



Applications



Flat shaped for working on flat grinding surfaces. Most efficient when used between 0° to 15° angle. Best choice for smooth finishing.

TECHNICAL DATA Type 27

Key	Icon	Grit
DW426110	115x22.23	100
DW426304	125x22.23	40
DW426306	125x22.23	60
DW426308	125x22.23	80
DW426310	125x22.23	100
DW426312	125x22.23	120
DW426504	180x22.23	40
DW426506	180x22.23	60
DW426508	180x22.23	80

CERAMIC FLAP DISC

INDUSTRIAL

Features

Premium ceramic
abrasive grain
Fiberglass backing
Heavy X-weight backing
Available with 11-"8/5 threaded hub



Applications

Flat shaped for working on flat grinding surfaces. Most efficient when used between 0° to 15° angle. Best choice for smooth finishing.



FLAP DISC

ZIRCONIA FLAP DISC

Features

Aluminum Oxide/
zirconia grain
Fiberglass backing
Heavy X-weight backing
Available with 11-"8/5 threaded hub



Applications



Conical shaped flaps are angled at 10° which is ideal for contour and edge work. Angled flaps provide greater surface contact for a more aggressive cut. Most efficient when used between 15° to 25° angle.

TECHNICAL DATA Type 29

Key	Icon	Grit
DW429106	115x22.23	60
DW429108	115x22.23	80
DW429304	125x22.23	40
DW429306	125x22.23	60
DW429308	125x22.23	80
DW429310	125x22.23	100
DW429312	125x22.23	120

ZIRCONIA FLAP DISC

Features

Aluminum Oxide /
Zirconia grain
Fiberglass backing
Heavy X-weight backing
Available with 11-"8/5 threaded hub



Applications



Flat shaped for working on flat grinding surfaces. Most efficient when used between 0° to 15° angle. Best choice for smooth finishing.

TECHNICAL DATA Type 27

Key	Icon	Grit
DW428104	115x22.23	40
DW428106	115x22.23	60
DW428108	115x22.23	80
DW428112	115x22.23	120
DW428304	125x22.23	40
DW428306	125x22.23	60
DW428308	125x22.23	80
DW428310	125x22.23	100
DW428312	125x22.23	120

DW428504	180x22.23	40
DW428506	180x22.23	60
DW428508	180x22.23	80

TECHNICAL DATA Type 27

Key	Icon	Grit
DW438104	115x22.23	40
DW438106	115x22.23	60
DW438108	115x22.23	80
DW438112	115x22.23	120
DW438304	125x22.23	40
DW438306	125x22.23	60
DW438308	125x22.23	80
DW438312	125x22.23	120

